

# Demco®

## FLEXplore Leg & Caster Assembly Instructions

### Required for leg assembly:

#2 Phillips screwdriver  
Rubber mallet

### Included for leg assembly:


(4) ¾" #10 Phillips screws  
(1) Allen wrench

### Step 1

Carefully remove outer packaging. Place tabletop facedown on a clean, non-scratching surface.

### Step 2

Set leg height using the Table Height Charts (below) as a guide. Use provided Allen wrench to tighten set screws. Check that all legs are set to the same height.



#### Desk/Table with Glides

Table Height	Leg Hole Number
21-3/4" High	1
22-3/4" High	2
23-3/4" High	3
24-3/4" High	4
25-3/4" High	5
26-3/4" High	6
27-3/4" High	7
28-3/4" High	8
29-3/4" High	9
30-3/4" High	10
31-3/4" High	11
32-3/4" High	12
33-3/4" High	13

### Caster Installation (optional)

*Skip to Step 3 if you are using glides*

Remove glides, using provided 9/16" wrench to loosen each nut before unscrewing. Attach casters, screwing one into each leg and tightening nut to secure.

#### Desk/Table with Casters

Table Height	Leg Hole Number
24-1/2" High	1
25-1/2" High	2
26-1/2" High	3
27-1/2" High	4
28-1/2" High	5
29-1/2" High	6
30-1/2" High	7
31-1/2" High	8
32-1/2" High	9
33-1/2" High	10
34-1/2" High	11
35-1/2" High	12
36-1/2" High	13

### Step 3

Heavy-duty steel brackets on the underside of the tabletop have been preinstalled for perfect leg positioning and quick, easy assembly.

For each leg: Turn leg upside down and slide fully into preinstalled bracket. Gently tap leg into position with rubber mallet if needed. Insert Phillips screw through slotted center hole and screw into tabletop. Tighten fully.

Once legs are secure, get help turning table upright.

Adjust nylon glides or casters to level table.

